



SOLAR STIK®

Expander Pak 1000

12 VDC – Item # 21-0101103

24 VDC – Item # 21-0102202

Overview

Powerful

The Expander Pak is a battery that holds up to 1.0 kWh of energy. It can also be used independently and includes terminal posts for recharging.

Durable

The Expander Pak is ruggedized for extreme environmental conditions and built to withstand severe impacts.

Scalable

If additional energy storage is required, battery capacity can be increased by using Plug & Play connections to add Power Paks (includes solar charge controller) or Expander Paks.

Field Serviceable

Innovative in design, no routine maintenance is required on the Expander Pak. The Pak is “field serviceable” using simple tools. The battery can be easily and quickly replaced at the end of its service life.



Exterior may appear different, depending on the 12 or 24 V version selected.

Features

- 1.0 kWh of energy storage
- State of charge and cycle life indicator
- Extremely durable and weatherproof
- Plug & Play

Why Solar Stik?

Modular designs
Scalable system
Field tested
24/7 Tech Support



© 2016 Solar Stik, Inc.
All Rights Reserved. Solar Stik is a registered trademark of Solar Stik, Inc.

SS20161010

800.793.4364
info@solarstik.com
www.solarstik.com



SOLAR STIK®

Expander Pak 1000

12 VDC – Item # 21-0101103

24 VDC – Item # 21-0102202

Case Color Options



Tan*



Black

* Indicates standard color

General

Energy Storage	1.0 kWh
Battery	(2) 12 V Lead-acid AGM
Amp Hour	<ul style="list-style-type: none"> • 80 Ah (12 VDC) • 40 Ah (24 VDC)
Operating Voltage	<ul style="list-style-type: none"> • 10.5–14.5 VDC (12 VDC) • 21.0–29.0 VDC (24 VDC)
Cycle Life	500 (80% depth of discharge)
Features	<ul style="list-style-type: none"> • State of charge (SOC) LED indicator • Cycle life indicator display
User Interface	LCD and push-button menu controls
Case	Pelican 1440 case with lid organizer
Warranty	1-year warranty on materials and workmanship

Safety

Breakers	100 A master circuit breaker
----------	------------------------------

Connections

	12 VDC Version	24 VDC Version
Post Terminal	(1) Interior 12 V post terminals with ergonomic twist knobs	(1) Interior 24 V post terminals with ergonomic twist knobs
Inter-Connect Port	(2) Exterior 12 VDC	(2) Exterior 24 VDC

Environmental

Operating Temperature	-50 °C to +65 °C (-58 °F to +149 °F)
-----------------------	--------------------------------------

Weights and Dimensions

Dimensions	19.70 x 12.00 x 18.00 in (50 x 30.5 x 45.7 cm)
Weight	97 lb (44.0 kg)

Includes

- (1) Expander Pak 1000 (12 or 24 VDC)
- (1) 5-foot Inter-Connect Cable

