



SOLAR STIK®

NATO Omni Cable

6 ft – Item # 13-000023

25 ft – Item # 13-000024

Overview

The NATO Omni Cable transfers 24 VDC power between a NATO receptacle and any 24 VDC Inter-Connect port of Solar Stik equipment [e.g., between a military or tactical vehicle generator and a Power Hub, Power Pak, Expander Pak or Power Distribution Module (PDM)].

Uses include:

- Jump-starting a discharged Power Pak or Expander Pak
- Trickle-charging the onboard battery of an auto-start modified generator in a hybrid power system
- Trickle-charging the onboard battery of a military tactical vehicle using Solar Stik solar power systems
- Jump-starting tactical generators with a Power Pak or Expander Pak

NOTE: The NATO Omni Cable is not recommended for jump-starting tactical vehicles with a Power Pak or Expander Pak.



General	
Connections	<ul style="list-style-type: none">• NATO slave connect• 24 VDC posi-lock
Amp Rating	<ul style="list-style-type: none">• 6 ft cable – 100 A at 24 VDC max• 25 ft – 35 A at 24 VDC max
Weights and Dimensions	
Weight	<ul style="list-style-type: none">• 6 ft cable – 3 lb (1.36 kg)• 25 ft cable – 9 lb (4.08 kg)
Length	<ul style="list-style-type: none">• 6 ft (1.83 m)• 25 ft (7.62 m)

