

Simple Swap

The Li 2400 Battery Service Kit is a pre-wired and configured LiFePO₄ battery module that enables rapid, simple exhange of the battery in the 24VDC Li Expander Pak 2400 or 24VDC Li Power Pak 2400.

Energy Storage	2.4 kWh
Energy Density	73 Wh/kg
Battery	Lithium iron phosphate (LiFePO,)
Operating Voltage	24.0–28.8 VDC
Amp Hour	100 Ah
Average Voltage	25.6 VDC
Max Discharge	100 A continuous
Self Discharge	<5% per month
Cycle Life	≥3000 Cycles @ 1C to 80% of initial capacity
Memory	No memory effect
Features	LED Indicators / Green: LED "On", Red: LED "Fault"
Exterior/Housing	Gray, ABS plastic
Warranty	1-year warranty on materials and workmanship
Environmental	
Operating Temperature	-25 °C to +65 °C (-13 °F to +149 °F)
Charge Temperature	+5 °C to +45 °C (+41 °F to +113 °F)
Storage Temperature	-30 °C to +70 °C (-22 °F to +158 °F)

weights and Dimensions	
Dimensions	13.4 x 9.0 x 21.3 in (34 x 22.86 x 54.1 cm)
Weight	77 lb (35 kg)

Preliminary

Category: Energy Storage

Li 2400 Battery Service Kit

Item # 21-0001006



