

### 24VDC PDM Plus

Item # 20-0403305

### Overview

#### Powerful

The 24VDC PDM (Power Distribution Module) Plus is a power distribution system that provides energy for USB, CLA, and terminal-post devices. The PDM is capable of powering or recharging multiple 5 V, 12 V, and 24 VDC appliances simultaneously through a variety of receptacles on its faceplate. The PDM Plus also has a built-in, pure sine wave inverter to supply 120 VAC to power appliances up to 250 watts.

#### **Portable**

The PDM Plus is very portable and lightweight, weighing only 27 pounds.

#### **Simple**

The PDM Plus requires a connection to a 12 VDC or 24 VDC battery to function. Simply use the Inter-Connect Cable to connect to any Solar Stik, Power Hub, PRO-Verter, Power Pak, or Expander Pak.













#### **Features**

- Compatible with 5 V, 12 V, 24 VDC, and 120 VAC appliances
- Powers USB, CLA, and terminal-post devices
- Durable and water-resistant
- Lightweight
- Plug & Play

#### **Case Color Options**





\* Indicates standard color





## 24VDC PDM Plus

Item # 20-0403305

General	
Operating Voltage	21.0–29.0 VDC
Features	5-watt flexible light with interchangeable red and clear lenses
User Interface	Voltage meter
Case	Pelican 1520 case
Warranty	1-year materials and workmanship

Connections	
5-15R	(2) 120 VAC (up to 250 W)
Post Terminal	(1) Interior 24 V post terminals with ergonomic twist knobs
CLA	(6) 12 VDC
USB	(12) 5 VDC
Inter-Connect Port	(1) Exterior 24 VDC

Safety	
Breakers	<ul> <li>- 50 A master circuit breaker</li> <li>- USB reset</li> <li>- CLA reset</li> <li>- Light reset</li> <li>- VAC reset</li> </ul>

# Environmental -40 °C to +40 °

Operating Temperature  $\begin{vmatrix} -40 \text{ °C to } +40 \text{ °C} \\ (-40 \text{ °F to } +104 \text{ °F}) \end{vmatrix}$ 

#### **Weights and Dimensions**

Dimensions	19.78 x 15.77 x 7.41 in (50.2 x 40 x 18.8 cm)
Weight	27 lb (12.2 kg)

#### Includes

- (1) 24VDC PDM Plus
- (1) 5-foot Inter-Connect Cable



