



SOLAR STIK®

# PRO-Verter 2300

## Overview

The Portable Remote Operation Inverter/Charger (PRO-Verter) provides a single point of power management, control, and distribution to a portable, battery-based, electrical circuit. The “open-architecture” design of the PRO-Verter allows the operator to network multiple power generation technologies into a single operational system that supports a specific application with clean, uninterrupted power.

PRO-Verter can be custom designed to integrate with any world-standard AC grid power, DC power generation source (i.e., solar or wind via a DC Power Hub), or fuel-driven generator to supply AC and DC power for any application. The PRO-Verter supplies power to the load by drawing directly from the batteries in the system while simultaneously receiving power input from a fuel-powered generator (optional) or from DC power generation sources to charge the batteries. When inverting, the PRO-Verter 2300 can provide 1500 watts continuous, modified sine wave AC power. Power output ports can be customized to meet user needs.

The PRO-Verter also allows remote monitoring. Sold as an accessory, the optional Remote Monitoring Kit (RMK) transmits real-time system information over any LAN or internet gateway.

The PRO-Verter 2300 can be used in multiple situations:

- When a primary battery is used in the electrical circuit
- If reduction of fuel generator “runtime” is necessary
- When supplemental (generator or grid) power is required for a renewable power system



*Exterior may appear different depending on the custom port types selected.*

## Features

- Compatible with 1.0–3.0 kW generators
- Auto Generator Start (non-AGS also available)
- LCD user interface
- Information Plate (I-Plate)—critical information at a glance: PRO-Verter function and system-specific integration
- Plug & Play setup and operation

## Case Color Options



\* Indicates standard color





# SOLAR STIK®

# PRO-Verter 2300

## Energy Storage Requirements

Energy Storage | 5 kWh minimum

## Power Generation Options

Power Hub | Solar and wind

Generator | 1-3 kW recommended

Grid Power | 50 or 60 Hz

## Custom Port Type Examples\* (AC In/Out)

Port Type	NEMA	Amps	Voltage
	5-15P 5-15R	15 A	125 VAC
	L5-30P L5-30R	30 A	125 VAC
	L5-50P L5-50R	50 A	125 VAC
	L15-20P L15-20R	20 A	250 VAC
	L14-30P L14-30R	30 A	125/250 VAC

\*Connectors with specifications appropriate for any world region are available. For more information about other port types and their capabilities, please contact us.

## Remote Monitoring Kit (Optional)

Complete System Monitoring	<ul style="list-style-type: none"> <li>• Current status</li> <li>• 24-hour running average</li> <li>• Historical</li> </ul>
Connectivity	<ul style="list-style-type: none"> <li>• Ethernet (TCP/IP)</li> <li>• Wireless (optional)</li> </ul>

## Weights and Dimensions

Case	Pelican 1550 case
Weight	35 lb (15.9 kg)
Dimensions	20.62 x 16.87 x 8.12 in (52.4 x 42.8 x 20.6 cm)

## General

Input Battery Voltage	18–32 VDC
Breakers	25 A 120 VAC Out   35 A 120 VAC Input   15 A DC Reset
User Interface	LCD for system monitoring and programming
Warranty	1-year materials and workmanship

## Inverter Specifications

Normal AC Output Voltage	120 VAC ± 5%
Output frequency	60 Hz ± 0.1%
Surge Power	1900 W
Continuous Output Power	1500 W
Waveform	Modified sine wave

## DC Charger Specifications

Normal DC Output Voltage	24 V
Continuous Output Current	35 A DC

## Connections

AC Input	(1) AC input port (Specified by customer, see "Custom Port Type Examples")
AC Output	(1 or 2) Output receptacles (Specified by customer, see "Custom Port Type Examples")
DC Input/Output	(1) Inter-Connect port for additional DC bus, converter, or Power Hub
DC Output	(2) 12 VDC receptacles supply up to 150 watts of power to 12 VDC appliances
Battery Input	(1) Inter-Connect port for battery, Power Pak, or Expander Pak

## Environmental

Operating Temperature	-20 °C to 60 °C (-4 °F to 140 °F)
Operating Humidity	0 to 95% RH noncondensing
Cooling	Fan cooled

